

## Pegasus® Granular

0-0-62

Chemical Composition			
Component	Symbol	Typical	Guarantee
Potassium Oxide Equivalent	K <sub>2</sub> O	62.4 %	62% Minimum
Potassium Chloride	KCl	98.8 %	
Sodium Chloride	NaCl	1.0 %	
Chloride	Cl <sup>-</sup>	47.6 %	
Moisture	$H_2O$	0.04 %	

Particle Size Dis	stribution Cumu	ulative %		
Tyler Mesh	US Mesh	Opening (mm)	Typical Range	Typical
4	4	4.75	0 - 2	0.4
5	5	4.00	3 - 15	6
6	6	3.35	20 - 50	30
7	7	2.80	50 - 75	61
8	8	2.36	75 - 95	86
9	10	2.00	93 - 100	96
10	12	1.70	97 - 100	98

Physical Properties				
Parameter	Typical			
Bulk Density (Loose)				
- lb/ft³	65			
- kg/m³	1041			
Angle of Repose	36 Degrees			

Typical
300
51

## Please refer to the Safety Data Sheet (SDS #: MOS100052) for additional information (www.mosaicco.com)

The information contained in this data sheet is a representation of the average properties of product analyses as tested on composite samples and typical analyses should not be considered a guaranteed specification. Individual shipment and grab sample analyses may fall outside of the above typical values Additional handling, transportation, or improper/extended storage may affect product analyses. Mosaic disclaims any responsibility or liability for any loss or damage that may occur from any reliance on, or other use of, the above information with respect to the product.